



35	non-self-resetting thermal cut-out	KSD301-R/250V/16A	1
34	relay	380-400V/25A	1
33	Heating element	230V 5000W	3
32	Re-set thermostat	KSD301/250V/16A	1
31	Adjustable thermostat	YT-WN16 250V/16A	1
30	Time delay thermostat	250V 10A K45	1
29	capacitance	CBB61/450V	1
28	Switch	250V 16A	1
27	Moter	400v	1
26	Fan	Ø300	1
25	Inner Casing	SECC	1
24	Outer casing	SPCC	1
23	Upper support of heating element	SECC	3
22	Under support of heating element	SECC	1
21	Inner casing holder	SECC	6
20	Cover of the grill	SPCC	1
19	The blades clamp	SECC	1
18	Back cover of control box	SPCC	1
17	Front cover of control box	SPCC	1
16	Plug Panel	SPCC	1
15	Control panel	SPCC	1
14	Middle panel	SECC	1
13	Upper cover	SPCC	1
12	Components of the wind	SPCC	1
11	Back grill	SPCC	1
10	Front grill	SPCC	1
9	Right stand	SPCC	1
8	Left stand	SPCC	1
7	Axis	SECC	1
6	Metal handle	SPCC	1
5	Wheel	PP+PTR	2
4	Tube cap	PA	2
3	Fixed screws	M8*35mm	2
2	Industrial Plug	400V 32A	1
1	Knob	PA	2
Key No.	Description	Material / Specifications	QTY

Project	BG-C15/3-19G(2022年状态)	Part No.		Parameter	
Designer		Standard	Units	m m	
Check		Approval	Scale		
Ningbo Baogong Electrical Appliance Co.,Ltd.			Model Name	Exploded diagram	
			Drawing No.	BG-C15/3-19G-BZ	